



LE1700 STANDARD TABLET PC

PRODUCT SPECIFICATIONS



Chassis	<ul style="list-style-type: none">• Polycarbonate - upper bezel• Magnesium Alloy - lower bezel	Weight	<ul style="list-style-type: none">• 3.3 lbs. with Standard Battery²• 4.3 lbs. with Extended Battery³
Operating Systems	<ul style="list-style-type: none">• Microsoft® Windows® XP Tablet PC Edition 2005• Microsoft® Windows Vista™ Business	Batteries	<ul style="list-style-type: none">• Standard Battery<ul style="list-style-type: none">- Lithium-ion battery with 38.5Whr capacity- Battery Life: ~3 hours• Optional Extended Battery<ul style="list-style-type: none">- Lithium-polymer with 40Whr capacity• Combined battery capacity<ul style="list-style-type: none">- Maximum 78.5Whr- Battery life: ~6-7 hours
Processors/Cache	<ul style="list-style-type: none">• Intel® Core™ 2 Duo Processor Low Voltage L7400 (4MB of L2 cache, 1.5GHz, 667MHz FSB)• Intel® Core™ Solo Processor Ultra Low Voltage U1400 (2MB L2 cache, 1.2GHz, 533MHz FSB)	Battery Charging Times	<ul style="list-style-type: none">• Standard Battery only<ul style="list-style-type: none">- 1.5 hours (Tablet PC on/off)⁴• Standard Battery with Extended Battery attached<ul style="list-style-type: none">- 3.5 hours (Tablet PC on/off)⁴
Chipset	<ul style="list-style-type: none">• Intel® 945GM Express	System Status LEDs	<ul style="list-style-type: none">• Power on/off• Battery status
Display Options	<ul style="list-style-type: none">• 12.1" SXGA+ display• 12.1" SXGA+ View Anywhere® display• 12.1" XGA View Anywhere display	Control Buttons	<ul style="list-style-type: none">• One 5-way directional control button• One function button, one programmable escape button and two programmable buttons• Secure Attention Sequence (SAS) button• Wireless on/off button
Graphics	<ul style="list-style-type: none">• Intel® Graphics Media Accelerator 950	AC Adapter	<ul style="list-style-type: none">• 50W universal, 3-pin jack• 100-240V 1.5a, 50-60Hz
Video RAM	<ul style="list-style-type: none">• Maximum 224MB total with Intel Dynamic Video Memory Technology	System Software	<ul style="list-style-type: none">• Motion Dashboard control panel• Motion/Softex OmniPass™ Security software• Infineon Security Platform Tools• Toshiba Bluetooth Software• Adobe® Acrobat® Reader• Windows Journal• Sticky Notes• Pen/button-based setup utility
Audio Controller	<ul style="list-style-type: none">• Intel® High Definition Audio	Environmental	<ul style="list-style-type: none">• Temperature<ul style="list-style-type: none">- Operation: +5°C to +35°C- Storage: -20°C to +60°C• Humidity<ul style="list-style-type: none">- Operating humidity: 8% to 80% without condensation- Storage humidity: 8% to 90% without condensation• Altitude<ul style="list-style-type: none">- Operation: sea level 0 to 10K ft.- Storage: sea level 0 to 40K ft.
PC Card Controller	<ul style="list-style-type: none">• Industry-standard CardBus controller	Standards	<ul style="list-style-type: none">• ACPI 2.0 compliant
System Memory	<ul style="list-style-type: none">• Base RAM: 1GB (2 x 512MB) 667MHz DDR2 memory with Dual Channel memory support- Upgradeable to a maximum of 4GB	Regulatory	<ul style="list-style-type: none">• AS/NZS 3548:1995• FCC Part 15 Subpart B Class B• FCC Part 15 Subpart C• FCC part 15 Subpart E• FCC part 22 H• FCC part 24 E• FCC OET65 Supplement C (01-01)• CAN/CSA RSS-102 Safety Code 6• CAN/CSA ICES-003 Class B• CAN/CSA RSS-210• Industry Canada: RSS-133• Industry Canada : RSS-129• CE: EN55011, EN55022, EN55024, EN301-489-17, EN301-893, EN300-328• CE: R&TTE (89/336/EC) & R&TTE (99/5/EC)• CE: EN 50392:2004 / IEC 62209-1:2005
System Storage	<ul style="list-style-type: none">• 1.8" Hard Disk Drive (HDD) with 40GB or 80GB capacities• PCI bus master enhanced IDE• Supports Ultra ATA 66/100• 4200 RPM	Safety	<ul style="list-style-type: none">• UL, CUL, TUV (EN/IEC 60950-1 A11/2004)
Communications	<ul style="list-style-type: none">• Integrated Ev-DO Rev. A Novatel Wireless ES725 Wireless Wide Area Network Module¹ (optional)• Atheros 802.11a/b/g card• Intel PRO/Wireless 3945 a/b/g card (optional)• Integrated 10/100/1000 Ethernet LAN controller with RJ-45 connector (Gigabit Ethernet)• Integrated Bluetooth®	Warranty	<ul style="list-style-type: none">• Standard 1-year warranty• Multi-year options available
Audio	<ul style="list-style-type: none">• Motion Speak Anywhere® technology<ul style="list-style-type: none">- Multi-directional array microphone design intelligently switches between two of the three microphones based on screen orientation- Knowles Acoustics IntelliSonic software• Two integrated speakers		
I/O Ports	<ul style="list-style-type: none">• Microphone-in• Headphone-out• Two USB 2.0 ports• DVI-D custom connector• IrDA port• External VGA port• Motion accessory port• RJ-45 connector• Docking connector• DC power in		
Expansion Card Slots	<ul style="list-style-type: none">• Secure Digital (SD) slot• One Type I or Type II PC card slot• SIM card slot		
Security	<ul style="list-style-type: none">• Integrated Fingerprint Reader• TCG Trusted Platform Module (TPM)• Universal lock slot• ComputraceComplete (optional)• Motion DataGuard™		
Dimensions	<ul style="list-style-type: none">• 11.65" x 9.64" x 0.74" - 0.87" (296mm x 245mm x 18.7 - 22mm)		

For more information and localized websites, please visit www.MotionComputing.com

1-866-MTABLET

¹Not available in Canada.

²Weight represents approximate system weight measured with a 38.5Whr battery, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

³Weight represents approximate system weight measured with both the 38.5Whr Standard Battery and a 40Whr Extended Battery attached, empty PCMCIA slot and no pen. Actual system weight may vary depending on component and manufacturing variability.

⁴Approximate charging time. Validated charging from 5% to 90% with system on or system off.